



### Alu-Festkupplung mit Innengewinde System Storz

Material Aluminium  
Dichtung Nitril-Kautschuk

NW		IG	Knaggenabstand (mm)	Anzahl Knaggen	Best.-Nr.
25-D		1/2"	31	2	2101 025013
25-D		3/4"	31	2	2101 025019
25-D	DIN 14 306	1"	31	2	2101 025025
38		1 1/2"	52	2	2101 038038
52-C		3/4"	66	2	2101 052019
52-C		1"	66	2	2101 052025
52-C		1 1/4"	66	2	2101 052032
52-C		1 1/2"	66	2	2101 052038
52-C	DIN 14 307	2"	66	2	2101 052050
52-C		2 1/2"	66	2	2101 052063
65		2"	81	2	2101 065050
65		2 1/2"	81	2	2101 065063
65		3"	81	2	2101 065075
75-B		2"	89	2	2101 075050
75-B	DIN 14 308	2 1/2"	89	2	2101 075063
75-B		3"	89	2	2101 075075
90		3"	105	2	2101 090075
100		4"	115	2	2101 100100
110-A		4"	133	2	2101 110100
125		4"	148	2	2101 125100
125		5"	148	2	2101 125125
150-F		6"	160	3	2101 150150