



COBIFLEX PRO

High-grade, crease resistant PVC water hose, twist free

suitable as standard waterhose for irrigation, gardening, agriculture, industry and construction

Temperature range

-15°C up to +60°C

Internal lining

PVC, black, smooth

External Cover

PVC, yellow, smooth

Inlays

pressure-resistant double tricot polyester inlay

| inner-Ø (mm) | wall (mm) | outer-Ø (mm) | WP (bar) | BP (bar) | weight (g/m) | length (m) | unit | order-no. |
|-----------------|--------------|-----------------|-------------|-------------|-----------------|---------------|------|-------------|
| 12,5 | 2,25 | 17 | 14 | 27 | 140 | 25 | m | 1010 012025 |
| 12,5 | 2,25 | 17 | 14 | 27 | 140 | 50 | m | 1010 012050 |
| 19 | 2,8 | 24,6 | 12 | 24 | 260 | 25 | m | 1010 019025 |
| 19 | 2,8 | 24,6 | 12 | 24 | 260 | 50 | m | 1010 019050 |
| 19 | 2,8 | 24,6 | 12 | 24 | 260 | 100 | m | 1010 019100 |
| 25 | 3,4 | 31,8 | 9 | 17 | 410 | 25 | m | 1010 025025 |
| 25 | 3,4 | 31,8 | 9 | 17 | 410 | 50 | m | 1010 025050 |
| 25 | 3,4 | 31,8 | 9 | 17 | 410 | 100 | m | 1010 025100 |
| 32 | 4 | 40 | 6 | 12 | 620 | 25 | m | 1010 032025 |