



## COBICOOL EPDM-radiator hose

suitable for passing water in the cooling circuit. Resistant to a variety of antifreeze.

Temperature range	-35°C up to +100°C
Internal lining	EPDM, black, smooth
External Cover	EPDM, black, fabric figured
Inlays	textile fabric
Safety	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	BP (bar)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
15	3	21	4	12	105	260	40	m	1015 015000
18	3	24	4	12	126	300	40	m	1015 018000
20	3,5	27	4	12	160	360	40	m	1015 020000
25	4	33	3	9	200	510	40	m	1015 025000
30	4	38	3	9	240	600	40	m	1015 030000
32	4	40	3	9	256	630	40	m	1015 032000
35	4	43	3	9	280	690	40	m	1015 035000
38	4	46	3	9	304	740	40	m	1015 038000
40	4	48	3	9	320	770	40	m	1015 040000
42	4	50	3	9	336	810	40	m	1015 042000
50	4	58	3	9	400	950	40	m	1015 050000
60	4	68	3	9	480	1120	40	m	1015 060000
63	5	73	3	9	504	1430	40	m	1015 063000
65	5	75	3	9	520	1480	40	m	1015 065000
85	6	97	3	9	680	2300	40	m	1015 085000
90	6	102	3	9	720	2080	40	m	1015 090000
100	6	112	3	9	800	2600	40	m	1015 100000
110	6	122	3	9	880	2930	40	m	1015 110000