



COBIDRUCK LIGHTFLEX

Highly flexible rubber spiral suction and pressure hose

suitable for water, waste water, sewage and low concentrated alkalis and acids. For agriculture, construction and industry. Very flexible, robust and buckling stabilized pressure hose.

| | |
|--------------------------|---|
| Temperature range | -30°C up to +85°C |
| Internal lining | SBR, black, smooth, resistant to waste water with a pH of 5 to 10 |
| External Cover | SBR, black, corrugated, fabric figured, weather resistant |
| Inlays | steel wire spiral, textile inlay |
| Safety | 3:1 |

| inner-Ø (mm) | wall (mm) | outer-Ø (mm) | WP (bar) | vacuum (m WC) | bending radius (mm) | weight (g/m) | length (m) | unit | order.-no. |
|-----------------|--------------|-----------------|-------------|------------------|------------------------|-----------------|---------------|------|-------------|
| 50 | 6,5 | 63 | 6 | 9 | 150 | 1400 | 40 | m | 1029 050000 |
| 80 | 7 | 94 | 6 | 9 | 240 | 2310 | 20 | m | 1029 080000 |
| 100 | 7 | 114 | 6 | 9 | 300 | 3390 | 20 | m | 1029 100000 |
| 102 | 7 | 116 | 6 | 9 | 306 | 3610 | 20 | m | 1029 102000 |
| 127 | 8 | 143 | 6 | 9 | 445 | 4960 | 20 | m | 1029 127000 |
| 152 | 8 | 168 | 6 | 9 | 608 | 6430 | 20 | m | 1029 152000 |
| 203 | 10,5 | 224 | 6 | 9 | 812 | 11390 | 20 | m | 1029 203000 |