



COBIFLAT M

**COBIFLAT M**  
**Middle-heavy PVC flat hose**

suitable for construction trade, industry and agriculture. Ideally suited for irrigation. As an inlet and outlet hose for water and other media, flat rollable.

**Temperature range** -10°C up to +60°C

**Structure** PVC, inside and outside smooth, blue

**Inlays** with polyesteryarn inlay



inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	weight (g/m)	length (m)	unit	order-no.
32	2	36	6	220	100	m	1031 032000
38	1,8	41,6	6	300	100	m	1031 038000
52	1,8	55,6	6	400	100	m	1031 052000
52	1,8	55,6	6	400	50	m	1031 052050
63	1,8	66,6	6	580	100	m	1031 063000
63	1,8	66,6	6	580	50	m	1031 063050
76	1,8	79,6	6	700	100	m	1031 076000
76	1,8	79,6	6	700	50	m	1031 076050
90	1,6	93,2	4	700	100	m	1031 090000
102	1,6	105,2	4	800	100	m	1031 102000
102	1,6	105,2	4	800	25	m	1031 102025
102	1,6	105,2	4	800	50	m	1031 102050
110	1,6	113,2	4	900	100	m	1031 110000
110	1,6	113,2	4	900	50	m	1031 110050
127	1,9	130,8	4	1000	100	m	1031 127000
127	1,9	130,8	4	1000	50	m	1031 127050
152	1,6	155,2	4	1150	100	m	1031 152000
152	1,6	155,2	4	1150	50	m	1031 152050
204	1,7	207,4	4	1900	50	m	1031 204050