



COBISINTEC 13

Synthetic construction and industry hose

suitable as construction site hose and for water duct. All-weather flat hose, rot-proof, abrasion-resistant and durable. Assembled with aluminium couplings system Storz with long tail.

Temperature range -20°C up to +80°C

Internal lining black, rubber-lined

External Cover double yarned polyester chain, uncoated, natural coloured, with racing stripes green, red, green

inner-Ø (mm)	KD (mm)	WP (bar)	BP (bar)	weight (g/m)	length (m)	unit	order.-no.
25-D	31	13	39	180	20	pcs.	1040 025020
52-C	66	13	39	380	5	pcs.	1040 052005
52-C	66	13	39	380	10	pcs.	1040 052010
52-C	66	13	39	380	15	pcs.	1040 052015
52-C	66	13	39	380	20	pcs.	1040 052020
52-C	66	13	39	380	25	pcs.	1040 052025
52-C	66	13	39	380	30	pcs.	1040 052030
65	81	13	39	365	20	pcs.	1040 065020
75-B	89	13	39	640	10	pcs.	1040 075010
75-B	89	13	39	640	15	pcs.	1040 075015
75-B	89	13	39	640	20	pcs.	1040 075020
75-B	89	13	39	640	25	pcs.	1040 075025
75-B	89	13	39	640	30	pcs.	1040 075030
102-A	133	13	39	900	20	pcs.	1040 102020
102-A	133	13	39	900	25	pcs.	1040 102025
102-A	133	13	39	900	30	pcs.	1040 102030