



## COBIINDIWA Rubber industrial water hose

suitable for water, waste water, sewage and low concentrated alkalis and acids. For applications in agriculture, construction and industry. Robust and buckling stabilized pressure hose.

<b>Temperature range</b>	-30°C up to +85°C
<b>Internal lining</b>	SBR, black, smooth, resistant to waste water with a pH of 5-10
<b>External Cover</b>	SBR, black, fabric figured
<b>Inlays</b>	textile inlay
<b>Safety</b>	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	BP (bar)	bending radius weight		length (m)	unit	order.-no.
25	5	35	10	30	200	590	40	m	1051 025000
32	6	44	10	30	262	920	40	m	1051 032000
38	6	50	10	30	304	1130	40	m	1051 038000
40	6	52	10	30	314	1290	40	m	1051 040000
45	7	59	10	30	360	1440	40	m	1051 045000
50	7	64	10	30	400	1750	40	m	1051 050000
60	8	76	10	30	493	2040	40	m	1051 060000
65	8	81	10	30	530	2770	40	m	1051 065000
76	8	92	10	30	622	2530	40	m	1051 076000
102	8	118	10	30	816	3330	40	m	1051 102000
127	10	147	10	30	1030	5290	20	m	1051 127000
152	11	174	10	30	1245	6220	20	m	1051 152000