



COBISAUG

Highly flexible rubber spiral suction hose with spiral free cuffs

suitable for agriculture, construction trade and industry. Suitable for water, waste water, sewage and low concentrated alkalis and acids. Both sides smooth and spiral free cuffs.

Temperature range	-30°C up to +85°C
Internal lining	SBR, black, smooth, resistant to waste water with a pH of 5-10
External Cover	SBR, black, corrugated, fabric figured
Inlays	steel wire spiral, textile inlay
Safety	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
32	4	40	3	9	96	960	3	pcs.	1052 032030
50	5	60	3	9	153	1480	6	pcs.	1052 050060
60	5	70	3	9	180	1610	1	pcs.	1052 060010
65	6	77	3	9	195	1800	4	pcs.	1052 065040
70	6	82	3	9	210	1990	0,5	pcs.	1052 070005
75	6	87	3	9	225	2340	3	pcs.	1052 075030
75	6	87	3	9	225	2340	5	pcs.	1052 075050
75	6	87	3	9	225	2340	6	pcs.	1052 075060
80	7	94	3	9	240	2590	1	pcs.	1052 080010
80	7	94	3	9	240	2590	3	pcs.	1052 080030
90	7	104	3	9	270	3160	1	pcs.	1052 090010
90	7	104	3	9	270	3160	3	pcs.	1052 090030
100	7	114	3	9	300	3270	2	pcs.	1052 100020
100	7	114	3	9	300	3270	3	pcs.	1052 100030
100	7	114	3	9	300	3270	4	pcs.	1052 100040
100	7	114	3	9	300	3270	5	pcs.	1052 100050
110	7	124	3	9	330	4310	1	pcs.	1052 110010
110	7	124	3	9	330	4310	2	pcs.	1052 110020
110	7	124	3	9	330	4310	3	pcs.	1052 110030
110	7	124	3	9	330	4310	4	pcs.	1052 110040
120	8	136	3	9	360	4200	3	pcs.	1052 120030
125	9	143	3	9	381	5360	2	pcs.	1052 125020
125	9	143	3	9	381	5360	3	pcs.	1052 125030
125	9	143	3	9	381	5360	5	pcs.	1052 125050
133	9	151	3	9	399	5760	0,5	pcs.	1052 133005
133	9	151	3	9	399	5760	2	pcs.	1052 133020
133	9	151	3	9	532	5670	3	pcs.	1052 133030
150	10	170	3	9	456	6680	2	pcs.	1052 150020
150	10	170	3	9	456	6680	3	pcs.	1052 150030
150	10	170	3	9	456	6680	4	pcs.	1052 150040
150	10	170	3	9	456	6680	5	pcs.	1052 150050
159	10	179	3	9	636	7770	2	pcs.	1052 159020
200	12	224	3	9	800	14140	4	pcs.	1052 200040
200	12	224	3	9	800	14140	5	pcs.	1052 200050