



COBILIGHT



COBILIGHT

PVC suction and pressure hose for light applications

suitable for conveying of water, waste water and feces in the agriculture and industry, irrigation and draining. Light and flexible quality. Resistant to many chemicals, UV and weather resistant.

Temperature range -15°C up to +60°C

Structure synthetic spiral hose, green transparent, inside smooth with embedded white hard PVC spiral, outside light corrugated

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
19	2,4	23,8	7	7	85	220	50	m	1060 019000
20	2,4	24,8	5	6	100	250	50	m	1060 020000
20	2,4	24,8	5	6	100	250	25	m	1060 020025
25	2,4	29,8	6	7	105	250	50	m	1060 025000
30	2,5	35	6	7	120	340	50	m	1060 030000
32	2,6	37,2	6	7	130	345	50	m	1060 032000
38	3	44	6	7	155	470	50	m	1060 038000
40	3	46	5	7	165	500	50	m	1060 040000
45	3,2	51,4	5	7	195	550	50	m	1060 045000
51	3,6	58,2	5	7	205	680	50	m	1060 051000
60	3,6	67,2	4	7	250	950	50	m	1060 060000
63	3,7	70,4	4	7	260	980	50	m	1060 063000
70	3,9	77,8	4	7	295	1000	50	m	1060 070000
76	4,1	84,2	4	6	320	1150	50	m	1060 076000
80	4,5	89	3	6	335	1200	50	m	1060 080000
90	4,8	99,6	3	6	390	1800	50	m	1060 090000
102	5,4	112,8	3	6	430	2000	50	m	1060 102000