



COBIFOOD STAR SP Milk handling hose

for liquid, fatty and non-fatty foods such as wine, beer, milk, juice, alcohol up to 96%. Equipment of unloading stations, stationary processing and filling plants, silo vehicles and as a milk collection hose.

Temperature range	-30°C up to +80°C, sterilizable with steam up to max.+120 °C (max. 30 min)
Internal lining	synthetic special elastomer, white, mirror-smooth, odorless and tasteless
External Cover	special synthetic elastomer, blue, fabric-patterned, non-marking
Inlays	synthetic textile inlays with steel spirals
Regulation/Licenses	EU-regulation no. 1935/2004, 2023/2006, FDA direction 21 CFR 177.2600., BfR recommendation XXI Kat. 2 D.M. 21/03/71
Safety	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order.-no.
25	5,5	36	10	9	90	700	40	m	1120 025000
32	5,5	43	10	9	122	850	40	m	1120 032000
38	6	50	10	9	135	1150	40	m	1120 038000
40	6	52	10	9	140	1210	40	m	1120 040000
45	6	57	10	9	260	1320	40	m	1120 045000
50	6	62	10	9	175	1460	40	m	1120 050000
65	6,5	78	10	9	230	2000	40	m	1120 065000
70	7	84	10	9	300	2510	40	m	1120 070000
76	7	90	10	9	410	2600	40	m	1120 076000