



COBIDUST KK PVC suction and blast hose

suitable for suction of air, fumes, gas, powders, sawing, dust. For aerating and conditioning plants, wood working plants, for agriculture as drill machine hose, for conveying of gaseous media. Very light and flexible quality. Resistant to atmospheric influences and chemical substances.

Temperature range -15°C up to +60°C

Structure soft PVC, grey, inside smooth, with embedded hard PVC spiral, outside corrugated

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
20	0,8 / 2,4	24,8	1	5	30	125	30	m	1263 020000
25	1 / 2,5	30	1	5	25	140	50	m	1263 025000
30	1 / 2,8	35,6	1	5	30	220	50	m	1263 030000
32	1 / 2,9	37,8	1	5	32	230	50	m	1263 032000
35	1 / 3	41	1	4	35	260	50	m	1263 035000
38	1 / 3,2	44,4	1	4	38	280	50	m	1263 038000
40	1 / 3,3	46,6	1	4	40	290	50	m	1263 040000
50	1 / 3,9	57,8	0,5	4	50	430	50	m	1263 050000
55	1 / 3,9	62,8	0,5	4	55	470	50	m	1263 055000
60	1 / 4	68	0,5	4	60	510	50	m	1263 060000
76	1,2 / 4,3	84,6	0,3	4	76	690	50	m	1263 076000
80	1,2 / 4,8	89,6	0,3	4	80	700	50	m	1263 080000
100	1,2 / 5,4	110,8	0,3	4	100	980	30	m	1263 100000
110	1,3 / 5,6	121,2	0,3	4	110	1400	30	m	1263 110000
120	1,3 / 5,6	131,2	0,3	4	120	1500	30	m	1263 120000
127	1,3 / 5,6	138,2	0,3	4	127	1250	30	m	1263 127000
150	1,3 / 6,1	162,2	0,3	4	150	1700	20	m	1263 150000
200	1,5 / 6,6	213,2	0,3	4	400	2400	20	m	1263 200000