



## COBIDUST L

### Super lightweight polyurethane suction and blast hose, antistatic

for vapours, small industrial cleaning and suction plants. Can be used as protection sleeve. Suitable for suction of smoke and deciduous gases, dust suction of dry food according to EU 10/2011. Very light, flexible and abrasion-proof quality. Resistant to mineral oils, ageing, ozone and atmospheric agents, axially compressible about 5:1. Antistatic in accordance with TRBS 2153 by grounding the spiral. Not resistant to microbes and hydrolysis.

**Temperature range** -40°C up to +90°C

**Structure** Ester based polyurethane, transparent, with coppered steel wire spiral, inside and outside corrugated

inner-Ø (mm)	wall (mm)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
38	0,4	2	30	175	10	m	1270 038000
40	0,4	2	32	185	10	m	1270 040000
45	0,4	2	36	205	10	m	1270 045000
51	0,4	0,2	40	230	10	m	1270 051000
60	0,4	1,7	50	265	10	m	1270 060000
63	0,4	1,7	55	275	10	m	1270 063000
65	0,4	1,7	56	285	10	m	1270 065000
70	0,43	1,7	60	375	10	m	1270 070000
76	0,43	1,7	65	405	10	m	1270 076000
80	0,43	1,6	65	420	10	m	1270 080000
90	0,43	1,6	75	470	10	m	1270 090000
102	0,53	1,3	85	530	10	m	1270 102000
110	0,53	1,2	90	570	10	m	1270 110000
120	0,53	1	100	620	10	m	1270 120000
127	0,63	1	105	755	10	m	1270 127000
130	0,63	0,8	105	770	10	m	1270 130000
140	0,63	0,8	115	830	10	m	1270 140000
152	0,63	0,8	125	890	10	m	1270 152000
160	0,63	0,7	130	935	10	m	1270 160000
180	0,63	0,5	150	1210	10	m	1270 180000
203	0,63	0,4	165	1360	10	m	1270 203000
228	0,63	0,4	185	1525	10	m	1270 228000
254	0,65	0,4	210	1845	10	m	1270 254000
305	0,65	0,3	250	2205	10	m	1270 305000
356	0,65	0,3	300	2570	10	m	1270 356000
406	0,75	0,3	350	3150	10	m	1270 406000