



COBISUPERFLEX TOP

High flexible rubber spiral suction and conveying hose with spiral free cuffs

with high abrasion-proof internal lining, suitable for abrasive media such as sand, grit, stones, fly ash, blasting agents. Both sides spiral free cuffs.

Temperature range	-30°C up to +85°C
Internal lining	NR, black, smooth, electrical conductive
External Cover	NR/SBR, black, cord ribbed, electrical conductive, fabric figured
Inlays	steel wire spiral, copper braid, textile inlay
Ohmic resistance	<10 high 6 Ω
Abrasion of lining	ca. 50 mm ³
Safety	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order.-no.
50	7	64	4	9	150	1430	40	m	1301 050000
60	7	74	3	9	180	1590	40	m	1301 060000
76	8	92	3	9	230	2380	40	m	1301 076000
80	8	96	3	9	240	2410	40	m	1301 080000
80	8	96	3	9	240	2410	5	pcs.	1301 080005
102	9	120	2	9	310	3970	20	m	1301 102000
102	9	120	2	9	310	3970	5	pcs.	1301 102005
127	9	145	2	9	380	4810	20	m	1301 127000
127	9	145	2	9	380	4810	5	pcs.	1301 127005
152	9	170	2	9	460	6080	20	m	1301 152000
152	9	170	2	9	460	6080	5	pcs.	1301 152005
203	11	225	2	9	820	9950	5	pcs.	1301 203005