



COBISUPERFLEX TOP LIGHT



COBISUPERFLEX TOP LIGHT

High flexible rubber spiral hose and conveying hose with spiral free cuffs

with high abrasion-proof internal lining, suitable for abrasive media such as sand, grit, stones, fly ash, blasting agents. Both sides with smooth, spiral free cuffs.

Temperature range	-30°C up to +85°C
Internal lining	NR, black, smooth, electrical conductive
External Cover	NR/BR, black, corrugated, electrical conductive, fabric figured
Inlays	steel wire spiral, copper braid, textile inlay
Ohmic resistance	<10 high 6 Ω
Abrasion of lining	ca. 50 mm ³
Safety	3:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
50	5	60	3	9	150	1380	40	m	1305 050000
80	5	90	3	9	240	2080	40	m	1305 080000
102	5,5	113	3	9	310	3330	20	m	1305 102000
102	5,5	113	3	9	310	3330	5	pcs.	1305 102005
127	5,5	138	3	9	380	4510	20	m	1305 127000
127	5,5	138	3	9	380	4510	5	pcs.	1305 127005
152	5,5	163	3	9	460	5250	20	m	1305 152000
152	5,5	163	3	9	460	5250	5	pcs.	1305 152005