



## COBISUPER PU PVC/PU suction and pressure hose for middle heavy applications

suitable for grain, powder, grinding and mixing plants. Very flexible and abrasion-proof PVC suction and pressure hose with internal polyurethane coat and internal copper braid.

<b>Temperature range</b>	-25°C up to +65°C
<b>Internal lining</b>	polyurethane, transparent, smooth
<b>External Cover</b>	PVC, transparent, with embedded orange hard PVC-spiral, light corrugated
<b>Inlays</b>	internal copper braid

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
90	7	104	2,5	8	350	2150	30	m	1324 090000
90	7	104	2,5	8	350	2150	3,6	pcs.	1324 090036
90	7	104	2,5	8	350	2150	4,9	pcs.	1324 090049
90	7	104	2,5	8	350	2150	5,1	pcs.	1324 090051
90	7	104	2,5	8	350	2150	5,6	pcs.	1324 090056
90	7	104	2,5	8	350	2150	5,9	pcs.	1324 090059
102	7,8	117,6	2	8	380	2700	30	m	1324 102000
102	7,8	117,6	2	8	380	2700	4	pcs.	1324 102040
102	7,8	117,6	2	8	380	2700	4,9	pcs.	1324 102049
102	7,8	117,6	2	8	380	2700	5,9	pcs.	1324 102059