



## COBIPUR R

### Middle heavy polyurethane exhaust ventilation hose, flame-retardant according to DIN 4102-B1, antistatic

suitable for wood shavings and wood exhaust ventilation. Conform to the safety regulations of the German Wood Trade Association. Not resistant to microbes and hydrolysis.

<b>Temperature range</b>	-40°C up to +90°C, for short time up to +125°C
<b>Structure</b>	Ester based polyurethane, transparent, with steel wire spiral, inside smooth, outside corrugated
<b>Regulation/Licenses</b>	flame-retardant according to DIN 4102-B1, UL94-V2
<b>Ohmic resistance</b>	permanently antistatic wall in accordance with ISO 8031 electrical and surface resistance <10 high 9 Ω and in accordance with TRGS 727 <2,5*10 high 8 Ω

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order.-no.
60	0,7 / 3,5	67	1	3,1	44	480	10	m	1326 060000
80	0,7 / 3,5	87	0,8	1,6	56	640	10	m	1326 080000
100	0,7 / 3,5	107	0,6	1,3	68	800	10	m	1326 100000
120	0,7 / 3,5	127	0,5	1,1	80	950	10	m	1326 120000
140	0,7 / 3,5	147	0,4	0,9	92	1090	10	m	1326 140000
150	0,7 / 3,5	157	0,4	0,7	98	1400	10	m	1326 150000
160	0,7 / 3,5	167	0,4	0,7	104	1500	10	m	1326 160000
180	0,7 / 3,5	187	0,3	0,6	116	1670	10	m	1326 180000
200	0,7 / 3,5	207	0,3	0,5	128	1860	10	m	1326 200000
250	0,7 / 3,5	257	0,2	0,4	158	2310	10	m	1326 250000
300	0,7 / 3,5	307	0,2	0,3	188	2770	10	m	1326 300000