



COBIORPU AS

Polyurethane exhaust ventilation hose, antistatic

suitable for powder, grain mixture, wood shaving, dust, isolating materials, grass and deciduous exhaust ventilation, food and chemicals. Very moveable and abrasion-proof PU hose for light applications. Microbes and hydrolysis resistant. Antistatic thanks to revolving cooper braid.

Temperature range -40°C up to +80°C

Structure Ether based polyurethane, transparent, with embedded food grade ivory hard PVC spiral inside smooth, outside corrugated

Inlays copperbraid

Regulation/Licenses Food grade according to FDA Reg. CFR 21 -Item 177.2600, EU-Regulation 10/2011, (classes A, B, C, D2)

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order.-no.
38	0,5 / 2,8	43,6	2	50	220	20	m	1341 038000
40	0,5 / 2,8	45,6	2	60	230	20	m	1341 040000
52	0,5 / 3,2	58,4	2	70	310	20	m	1341 052000
60	0,5 / 3,6	67,2	1,6	80	470	20	m	1341 060000
76	0,6 / 4	84	1,6	100	660	30	m	1341 076000
100	0,6 / 4,5	109	1,3	140	820	20	m	1341 100000