



## COBIORPU ME AS

### Polyurethane exhaust ventilation hose for middle heavy applications

for abrasive media such as pellets, granulates and dust. Finds optimal application in the plastic and ceramic Industry. Can be used in woodworking under severe conditions. Antistatic thanks to revolving copper braid. Resistant to a variety of chemical substances. UV, ozone and weather resistant. Not resistant to microbes and hydrolysis.

**Temperature range** -40°C up to +80°C

**Structure** Ester based polyurethane, transparent, inside smooth, outside corrugated, with embedded dark grey hard PVC spiral

**Inlays** copper braid

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
40	0,9 / 3,6	47,2	3	140	360	30	m	1343 040000
51	0,9 / 4,5	60	3	175	555	30	m	1343 051000
60	1 / 4,5	69	3	200	660	30	m	1343 060000
65	1 / 4,5	74	3	230	705	30	m	1343 065000
70	1 / 4,5	79	3	250	775	30	m	1343 070000
80	1 / 5	90	2,5	290	920	30	m	1343 080000
102	1 / 5,7	113,4	2,5	400	1310	30	m	1343 102000