



## COBITANK TW D - Oil- and petrol-resistant pressure hose according to EN 12115

Highly flexible pressure hose according to EN 12115, ideal for loading and unloading tanks, tank vehicles with unleaded fuels (EN228:2017) with an oxygen limit according to EEC 85/536 and an aromatic content of up to 50%. Suitable as a reel hose for tank vehicles. Can be used for technical oils, diesel oils (EN 590:2017), heating oils (DIN 51 603 parts 1 - 5) and mineral oil-based hydraulic oils.

<b>Temperature range</b>	-30°C up to +90°C
<b>Internal lining</b>	NBR, black, smooth, electrically conductive
<b>External Cover</b>	CR, black, fabric figured, electrically conductive, oil-resistant, ozone and weather-resistant, abrasion-resistant
<b>Inlays</b>	synthetic textile inlay, 2 cooper braid
<b>Regulation/Licenses</b>	EN 12115:2021, EN 1761:1999, TRbF 131/2:1992
<b>Ohmic resistance</b>	<10 high 6 Ω
<b>Safety</b>	4:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
19	6	31	16	100	750	40	m	1405 019000
25	6	37	16	120	850	40	m	1405 025000
32	6	44	16	150	1000	40	m	1405 032000