



COBICHEM PLUS UPE SL
Chemical suction and pressure hose UP-E inlay according to EN 12115, very flexible

for passing aggressive media, suitable for discharge of many chemicals, acids and alkalis. For loading and unloading of tankers and railway wagons and the chemical industry.

Temperature range	-35°C up to +100°C
Internal lining	polyethylen UP-E, mirror-smooth, black, electrical conductive
External Cover	CSM, black, corrugated, antistatic, fabric figured, weather- and ozon-resistant
Inlays	synthetic textile yarn, steel wire spiral, cooper braid
Regulation/Licenses	EN 12115
Ohmic resistance	<10 high 6 Ω
Safety	4:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	vacuum (m WC)	bending radius (mm)	weight (g/m)	length (m)	unit	order.-no.
19	6	31	16	9	57	570	40	m	1458 019000
25	6	37	16	9	75	720	40	m	1458 025000
32	6,5	45	16	9	96	1010	40	m	1458 032000
38	6,5	51	16	9	114	1170	40	m	1458 038000
50	8	66	16	9	200	2120	40	m	1458 050000
75	8	91	16	9	300	3540	40	m	1458 075000
100	8,5	117	12	9	400	4220	20	m	1458 100000