



COBIROKAN

Rubber tube cleaning hose 200 bar

light, abrasion-resistant and highly flexible rubber pipe cleaning hose ideal for cleaning narrow house connections. Also used as an inlet hose for camera TV inspection. Pressed with fittings on the one side AGR (MT) on the other side DKR (FT).

Temperature range	-40°C up to +70°C
Internal lining	synthetic rubber, black
External Cover	rubber, smooth, high abrasion-proof, black
Inlays	steel fabric
Safety	2,5:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	BP (bar)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
12,7	3,15	19	200	500	65	430	40	pcs.	1484 012040
12,7	3,15	19	200	500	65	430	50	pcs.	1484 012050
12,7	3,15	19	200	500	65	430	60	pcs.	1484 012060
12,7	3,15	19	200	500	65	430	80	pcs.	1484 012080
12,7	3,15	19	200	500	65	430	100	pcs.	1484 012100
12,7	3,15	19	200	500	65	430	120	pcs.	1484 012120
16	3,2	22,4	200	500	80	450	80	pcs.	1484 016080
16	3,2	22,4	200	500	80	450	120	pcs.	1484 016120

Other sizes and lengths available on request!