



COBIPOLYKAN 200

Synthetic sewer cleaning hose 200 bar

highly abrasion-resistant, buoyant, cut resistant and very flexible. Pressed with fittings on the one side AGR (MT) on the other side DKR (FT).

Temperature range	-20°C up to +40°C
Internal lining	polyester-elastomer
External Cover	polyurethane, smooth, highly abrasion-proof, orange
Inlays	2 synthetic fabrics
Safety	2,5:1

inner-Ø (mm)	wall (mm)	outer-Ø (mm)	WP (bar)	BP (bar)	bending radius (mm)	weight (g/m)	length (m)	unit	order-no.
13	4,75	22,5	200	500	80	290	40	pcs.	1485 013040
13	4,75	22,5	200	500	80	290	60	pcs.	1485 013060
13	4,75	22,5	200	500	80	290	80	pcs.	1485 013080
13	4,75	22,5	200	500	80	290	100	pcs.	1485 013100
13	4,75	22,5	200	500	80	290	120	pcs.	1485 013120
13	4,75	22,5	200	500	80	290	150	pcs.	1485 013150
13	4,75	22,5	200	500	80	290	160	pcs.	1485 013160
13	4,75	22,5	200	500	80	290	180	pcs.	1485 013180
13	4,75	22,5	200	500	80	290	200	pcs.	1485 013200
19,5	5,75	31	200	500	100	480	40	pcs.	1485 019040
19,5	5,75	31	200	500	100	480	60	pcs.	1485 019060
19,5	5,75	31	200	500	100	480	80	pcs.	1485 019080
19,5	5,75	31	200	500	100	480	120	pcs.	1485 019120
19,5	5,75	31	200	500	100	480	160	pcs.	1485 019160
19,5	5,75	31	200	500	100	480	200	pcs.	1485 019200
19,5	5,75	31	200	500	100	480	240	pcs.	1485 019240
25,2	6,65	38,5	200	500	150	714	80	pcs.	1485 025080
25,2	6,65	38,5	200	500	150	714	120	pcs.	1485 025120
25,2	6,65	38,5	200	500	150	714	150	pcs.	1485 025150
25,2	6,65	38,5	200	500	150	714	160	pcs.	1485 025160
25,2	6,65	38,5	200	500	150	714	180	pcs.	1485 025180
25,2	6,65	38,5	200	500	150	714	200	pcs.	1485 025200
25,2	6,65	38,5	200	500	150	714	240	pcs.	1485 025240
32,5	7,75	48	200	500	200	1010	80	pcs.	1485 032080
32,5	7,75	48	200	500	200	1010	120	pcs.	1485 032120
32,5	7,75	48	200	500	200	1010	150	pcs.	1485 032150
32,5	7,75	48	200	500	200	1010	160	pcs.	1485 032160
32,5	7,75	48	200	500	200	1010	180	pcs.	1485 032180
32,5	7,75	48	200	500	200	1010	200	pcs.	1485 032200
32,5	7,75	48	200	500	200	1010	240	pcs.	1485 032240

Other lengths and connection types available on request!