



COBIPRESS FLAT – Compressed air layflat hose, ready for use, crimped with compressed air couplings Rd 75

COBIPRESS FLAT – Compressed air layflat hose, hydraulically crimped with compressed air couplings with union nut Rd 75 x 1/6“.

Temperature range	-30°C up to +80°C
Internal lining	nitrile rubber, reinforced, oil-resistant, smooth, yellow
External Cover	polyurethane, smooth, yellow
Inlays	double fabric made of 100% high-tenacity polyester yarn

inner-Ø (mm)	NW	wall (mm)	WP (bar)	weight (g/m)	length (m)	order.-no.
52 mm / 2“	Rd 75 x 1/6“	5	40	24200	20	771228 452005
52 mm / 2“	Rd 75 x 1/6“	5	40	44200	40	771228 452006



COBIPRESS FLAT – Compressed air layflat hose, ready for use, crimped with compressed air couplings Rd 65

COBIPRESS FLAT – Compressed air layflat hose, hydraulically crimped with compressed air couplings with union nut Rd 65 x 1/6“.

Interchangeable and compatible with the “Atlas Copco” system.

Direct hose extension possible without a double nipple by unscrewing the union nut.

Temperature range	-30°C up to +80°C
Internal lining	nitrile rubber, reinforced, oil-resistant, smooth, yellow
External Cover	polyurethane, smooth, yellow
Inlays	double fabric made of 100% high-tenacity polyester yarn

inner-Ø (mm)	NW	wall (mm)	WP (bar)	weight (g/m)	length (m)	order.-no.
52 mm / 2“	Rd 65 x 1/6“	5	25	23200	20	771228 052003
52 mm / 2“	Rd 65 x 1/6“	5	25	43200	40	771228 052004